WO 2004/099306 PCT/US2004/013413

What is claimed is:

5

10

15

20

25

30

 A thermally conductive heat exchange structure comprising a polymer composite comprising a major proportion of fluorocarbon polymer and a minor proportion of boron nitride.

- The thermally conductive heat exchange structure of claim 1 wherein said
 polymer composite comprises from about 2 % to about 40 % by weight of
 B(N).
 - The thermally conductive heat exchange structure of claim 1 wherein said polymer composite comprises from about 5 % to about 15 % of BN.
 - 4. The thermally conductive heat exchange structure of claim 2 wherein said polymer composite comprises at least about 60% by weight of fluorocarbon polymer.
 - The thermally conductive heat exchange structure of claim 2 wherein said polymer composite comprises at least about 75% by weight of fluorocarbon polymer.
 - The thermally conductive heat exchange structure of claim 2 wherein said polymer composite comprises at least about 85% by weight of fluorocarbon polymer.
 - 7. The thermally conductive heat exchange structure of claim 2 wherein said polymer composite comprises from about 85% to about 98% by weight of fluorocarbon polymer.
 - The thermally conductive heat exchange structure of claim 1 wherein said polymer composite has a thermal conductivity of at least about 1.5 (W/m/K).
 - The thermally conductive heat exchange structure of claim 1 wherein said polymer composite has a thermal conductivity of at least to about 2 (W/m/K).
 - 10. The thermally conductive heat exchange structure of claim 1 wherein said polymer composite has a thermal conductivity of at least to about 2.5 (W/m/K).

WO 2004/099306 PCT/US2004/013413

11. The thermally conductive heat exchange structure of claim 1 wherein said polymer composite comprises from about 2 % to about 20 % by weight of B(N).